



2200 Series



| Seleccione Consulta | | Designación de rodamiento | Dimensión [mm] | | | | Capacidades de carga básica (kN) | | Clasificaciones de velocidad (rpm) | Peso (Kg) |
|---------------------|----|---------------------------|----------------|-----|------|--------|----------------------------------|-------|------------------------------------|-----------|
| | | | D | D | B | rs min | Cr | Cor | Grasa Petr6leo (Kg) | |
| 2200 | 10 | 30 | 14 | 0.6 | 7.3 | 1.59 | 19000 | 23000 | 0.047 | |
| 2201 | 12 | 32 | 14 | 0.6 | 7.6 | 1.73 | 17000 | 20000 | 0.051 | |
| 2202 | 15 | 35 | 14 | 0.6 | 7.7 | 1.85 | 15000 | 18000 | 0.06 | |
| 2203 | 17 | 40 | 16 | 0.6 | 9.8 | 2.41 | 13000 | 16000 | 0.088 | |
| 2204 | 20 | 47 | 18 | 1 | 12.6 | 3.3 | 12000 | 14000 | 0.14 | |
| 2204K | 20 | 47 | 18 | 1 | 12.6 | 3.3 | 12000 | 14000 | 0.137 | |
| 2205 | 25 | 52 | 18 | 1 | 12.3 | 3.45 | 10000 | 12000 | 0.157 | |
| 2205K | 25 | 52 | 18 | 1 | 12.3 | 3.45 | 10000 | 12000 | 0.153 | |
| 2206 | 30 | 62 | 20 | 1 | 15.2 | 4.5 | 8600 | 10000 | 0.256 | |
| 2206K | 30 | 62 | 20 | 1 | 15.2 | 4.5 | 8600 | 10000 | 0.25 | |
| 2207 | 35 | 72 | 23 | 1.1 | 21.5 | 6.6 | 7500 | 8800 | 0.392 | |
| 2207K | 35 | 72 | 23 | 1.1 | 21.5 | 6.6 | 7500 | 8800 | 0.382 | |
| 2208 | 40 | 80 | 23 | 1.1 | 22.3 | 7.35 | 6700 | 7900 | 0.493 | |
| 2208K | 40 | 80 | 23 | 1.1 | 22.3 | 7.35 | 6700 | 7900 | 0.482 | |
| 2209 | 45 | 85 | 23 | 1.1 | 23.2 | 8.15 | 6000 | 7100 | 0.54 | |
| 2209K | 45 | 85 | 23 | 1.1 | 23.2 | 8.15 | 6000 | 7100 | 0.528 | |
| 2210 | 50 | 90 | 23 | 1.1 | 23.2 | 8.45 | 5500 | 6400 | 0.583 | |
| 2210K | 50 | 90 | 23 | 1.1 | 23.2 | 8.45 | 5500 | 6400 | 0.569 | |
| 2211 | 55 | 100 | 25 | 1.5 | 26.5 | 9.9 | 5000 | 5800 | 0.787 | |
| 2211K | 55 | 100 | 25 | 1.5 | 26.5 | 9.9 | 5000 | 5800 | 0.769 | |

2200 Series

| | | | | | | | | | |
|-------|----|-----|----|-----|------|------|------|------|------|
| 2212 | 60 | 110 | 28 | 1.5 | 34 | 12.6 | 4600 | 5400 | 1.08 |
| 2212K | 60 | 110 | 28 | 1.5 | 34 | 12.6 | 4600 | 5400 | 1.06 |
| 2213 | 65 | 120 | 31 | 1.5 | 43.5 | 16.4 | 4200 | 5000 | 1.44 |
| 2213K | 65 | 120 | 31 | 1.5 | 43.5 | 16.4 | 4200 | 5000 | 1.41 |
| 2214 | 70 | 125 | 31 | 1.5 | 44 | 17.1 | 3900 | 4600 | 1.52 |
| 2215 | 75 | 130 | 31 | 1.5 | 44.5 | 17.8 | 3700 | 4300 | 1.58 |
| 2215K | 75 | 130 | 31 | 1.5 | 44.5 | 17.8 | 3700 | 4300 | 1.54 |
| 2216 | 80 | 140 | 33 | 2 | 48.5 | 19.9 | 3400 | 4000 | 1.99 |
| 2216K | 80 | 140 | 33 | 2 | 48.5 | 19.9 | 3400 | 4000 | 1.95 |
| 2217 | 85 | 150 | 36 | 2 | 58 | 23.6 | 3200 | 3800 | 2.54 |