


NKI Series



Seleccione Consulta		Teniendo No:	Dimensiones del límite (mm)				Capacidades de carga básica (kN)		Velocidad límite (rpm)	Masa
			D	Fw	D	C	Dinámico (Cr)	Estático (Cor)	Petróleo	Kg
NKI8	8	14	25	16	12400	11300	21500	46		
NKI9/12	9	12	19	12	6200	7002	21700	14.6		
NKI10/16	10	14	22	16	9808	10500	19650	27.3		
NKI12/20	12	16	24	20	14000	18400	21000	39		
NKI15/16	15	19	27	16	8847	12853	19100	38		
NKI15/20	15	19	27	20	12347	19053	19100	45.7		
NKI17/16	17	21	29	16	13000	18200	20000	41.4		
NKI20/16	20	24	32	16	10800	17000	16700	48.5		
NKI22/16	22	25	34	16	8721	15340	16200	50		
NKI25/30	25	29	38	30	31500	56000	14000	115		
NKI35/30	35	40	50	30	22200	51350	11134	165		
NKI40/20	40	45	55	20	22000	48000	10127	124		
NKI40/30	40	45	55	30	35000	86000	10127	184		
NKI42/20	42	47	57	20	26000	52500	9500	138		
NKI45/25	45	50	62	25	36000	70000	8567	218		
NKI45/35	45	50	62	35	41500	102000	8567	289		
NKI50/25	50	55	68	25	32000	78000	7890	262		
NKI55/35	55	60	72	35	48000	126800	7256	357		
NKI60/25	60	68	82	25	35500	85000	7156	388		