

Thrust spherical roller bearings



Seleccione Consulta Designacion			Dimensiones principales (mm)			Capacidades de límite de carga básica (KN)		Masa de carga (kilogramo)
			D	D	H	Cr	Cor	
29412 E	60	130	42	390	915	5000	2,6	
29413 E	65	140	45	455	1080	4800	3,2	
29414 E	70	150	48	520	1250	4300	3,9	
29415 E	75	160	51	600	1430	4000	4,7	
29416 E	80	170	54	670	1630	3800	5,6	
29317 E	85	150	39	380	1060	4000	2,75	
29417 E	85	180	58	735	1800	3600	6,75	
29318 E	90	155	39	400	1080	4000	2,85	
29418 E	90	190	60	815	2000	3400	7,75	
29320 E	100	170	42	465	1290	3600	3,65	
29420 E	100	210	67	980	2500	3000	10,5	
29322 E	110	190	48	610	1730	3200	5,3	
29422 E	110	230	73	1180	3000	2800	13,5	
29324 E	120	210	54	765	2120	2800	7,35	
29424 E	120	250	78	1370	3450	2600	17,5	
29326 E	130	225	58	865	2500	2600	9	
29426 E	130	270	85	1560	4050	2400	22	
29328 E	140	240	60	980	2850	2600	10,5	
29428 E	140	280	85	1630	4300	2400	23	
29230 E	150	215	39	408	1600	2800	4,3	

Thrust spherical roller bearings

29330 E	150	250	60	1000	2850	2400	11
29430 E	150	300	90	1860	5100	2200	28
29332 E	160	270	67	1180	3450	2200	14,5
29432 E	160	320	95	2080	5600	2000	32
29334 E	170	280	67	1200	3550	2200	15
29434 E	170	340	103	2360	6550	1900	44,5
29236 E	180	250	42	495	2040	2600	5,8
29336 E	180	300	73	1430	4300	2000	19,5
29436 E	180	360	109	2600	7350	1800	52,5
29338 E	190	320	78	1630	4750	1900	23,5